

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028307 A1**

(51) International Patent Classification<sup>7</sup>: **B64F 1/305**  
(21) International Application Number:  
PCT/SE2004/001351

(22) International Filing Date:  
21 September 2004 (21.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0302528-5 24 September 2003 (24.09.2003) SE

(71) Applicant (for all designated States except US): FMT INTERNATIONAL TRADE AB [SE/SE]; Dalaslingan 8, S-231 32 Trelleborg (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ANDERBERG, Nils-Erik [SE/SE]; Asbjer Gård, S-231 96 Trelleborg (SE).

(74) Agents: ÖRTENBLAD, Bertil et al.; Noréns Patentbyrå AB, Box 10198, S-100 55 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: A METHOD OF CONNECTING A PASSENGER BRIDGE TO AN AIRCRAFT, AND AN ARRANGEMENT TO THIS END.



(57) Abstract: The present invention relates to a method of connecting the outer end of a passenger bridge (4) to a door on an aircraft body, said door (A3-A5;A8,A9) being located on one side of the aircraft and sternwards of the aircraft wing (6), wherein the inner part (7) of the passenger bridge is connected to a terminal building (8) via a rotunda (9), wherein the outer part of the passenger bridge carries a cabin for connection to the aircraft at a door located thereon, wherein the passenger bridge is made mobile through the agency of a drive means (12) which rests against the hardstanding (11) of the airport through the medium of wheels (13, 14) and which passenger bridge comprises telescopic parts (16-19). The invention is characterised by locating the drive means (12) at the outer end of the inner part (7) of the passenger bridge (4); by pivoting the outer part (10) of the passenger bridge in a vertical plane relative to the inner part (7) of the passenger bridge (4); driving the passenger bridge by means of the drive means (12) from a parking position to a docking position subsequent to the aircraft being parked for connection

with the passenger bridge (4), wherein said drive means (12) is positioned close to the leading edge of the aircraft wing (6) while telescoping the inner part (7) of said bridge; and by thereafter swinging the outer part (10) of the passenger bridge downwards and telescoping said outer part to an end position in which said cabin (5) can be docked to the aircraft body. The invention also relates to an arrangement



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*